

ORDINANCE 1920

ORDINANCE OF THE TOWN OF LOS GATOS AMENDING ORDINANCE NO. 1844 RELATING TO THE MODIFICATION OF THE DEVELOPMENT STANDARDS WHICH EFFECTED ZONE CHANGE NO. 88 (UNIVERSITY/EDELEN HISTORIC DISTRICT)

The Town Council of the Town of Los Gatos does hereby ordain:

SECTION I

The district delineated on the attached map is hereby designated historically and culturally significant as the University/Edelen Historic District HD-86-1B.

SECTION II

The district is designated to be historically, architecturally, or aesthetically significant for the reasons listed below:

A. Property: University/Edelen District Boundaries:

North - Saratoga Avenue

South - Main Street

East - Los Gatos Creek

West - Old Southern Pacific Railroad

(see map - Exhibit A)

B. Historic Designation HD-86-1B

C. Description of Designation: District

D. Description of Characteristics which justify designation:

Historical:

The University/Edelen area was originally part of the Mason Tract. In September 1880, the area was subdivided into five parcels ranging from 6.75 acres to 10 acres. These parcels were further subdivided and became the Miles/Edelen Subdivision (The Vineyard Lots), the Hagerty Subdivision, the Quick Subdivision, the Bentley/Pierce Subdivision and the Engrish Subdivision which created the lots forming the University/Edelen Area. These subdivisions predated the turn of the century.

Architecture:

Victorian is predominant architecture, including informal wood frame cottages and impressive homes, intermixed with Craftsman/Bungalow style cottages built somewhat later. Also present in smaller numbers are Colonial Revival. Contributing structures are both residential and commercial. Individual architectural distinction is not as important in a historic district as the neighborhood entity created. The University/Edelen district has easily identifiable boundaries which add to its perception as a distinct neighborhood.

Significant Residential Structures:

Harry Perrin Home - 315 University Avenue: This house is estimated to have been built in 1895. The original owners were Harry and Theresa Perrin. Mr. Perrin was a brick mason and contractor and built the house with his own hands for his bride. They sold the house in 1906. Mr. Perrin later constructed the revetments for the Presidio of San Francisco. The house has been called "Honeymoon House." The home is an excellent example of romanesque style architecture.

In 1972 a major remodeling job was redone under the direction of Boris and Nancy Baranowski. The interior was redone and made into law offices. In 1989 the structure was significantly damaged by the earthquake and in 1990 the building under went major repair and the seismic retrofit was completed in 1991 by VSL Corporation.

Miles House (Los Gatos Museum Restoration Award, 1971), 130 Edelen: This Queen Anne, two-story Victorian was built by contractor-land developer O. E. Miles in 1886. The house was converted to a duplex in 1932 and was then reverted to a single-family house in 1963. The home was used as a movie set for the 1970 Orson Wells movie "The Toy Factory."

Skinkle House, 129 Edelen: This Queen Anne, two-story Victorian was built by pharmacist A. Skinkle, Jr., in 1890. He was co-owner of Watkins Skinkle Drug Store on Main Street and Santa Cruz Avenue. Skinkle was president, in 1895, of the Borad of Trade (forerunner to the Chamber of Commerce).

CONTRIBUTORS TO DISTRICT

<i>Street Address</i>	<i>Estimated Date of Construction</i>
91 Bentley	1910s
107 Edelen	1890s
110 Edelen	1930-50s
114 Edelen	20th century
117 Edelen	19th century
124 Edelen	1900s
217. Edelen	19th century
219 Edelen	1920s
233 Edelen	1890s
239 Edelen	1890s
252 Edelen	1910s
255 Edelen	1920s
258 Edelen	1920s
68 Miles	1920s
72 Miles	1890s
40 University	1901
112 University	1930s
123 University	1900s
205 University	1900s
210 University	1920s
217 University	1910s
229- University	N/A
230 University	1920s
241 University	1930s
242 University	1860s
245 University	1930s
250 University	1920s
251 University.	1930s
254 University	1890s
.266 University	1890s
313 University	1920s
324 University.	1920s
326 University	1920s

<u>Street Address</u>	<u>Estimated Date of Construction</u>
327 University	1890s
329 University	1920s
330 University	1900s
333 University	1910s
259 University	1940s
111 Edelen	1880-90s
118 Edelen	1890s
129 Edelen	1890s
130 Edelen	1886
260 Edelen	1880s
115 University	1910s
118 University	1880s ,
122 University	1870-80's
126 University	1880s
128 University	1890s
201 University	1890s
202 University	1870s
215 University	1880-90s
221 University	1920s
231 University	1930s
232 University	1920s
237 University	1880s
256 University	1880s
262 University	1890s
301 University	1910s
303 University	1910s
315 University	c.1895
321 University	1890s
350 University	N/A
611 University	1950s

Source : Historic Inventory Survey conducted by Anne Bloomfield.

Significant Commercial Structures:

Old Town - 50 University Avenue: The most popular commercial structure in the Historic District are located at Old Town (formerly the University Avenue School and Auditorium). The property was a school site from 1881 to 1964. At one time (1893-1908), the site included both a grammar school and high school. Although the structures have been remodeled over time, they still maintain the historic character and charm of the old school site.

The first school opened on August 8, 1881. The structure was added to in 1885 and an addition for a high school was constructed in 1893. A final addition was constructed in 1916.

The old building was demolished and a new one built in 1923. The original two-floor school built in 1923 was modeled after the early California-Spanish mission of San Juan Capistrano. The school was abandoned in 1961. The property was sold in 1964 and converted into a Fine Arts Center housing more than 50 shops and restaurants the school auditorium and was the home of California Actors Theater and other performance groups until 1982. Today, the stripped Spanish Colonial Revival stucco schoolhouse has been reconstructed to work neatly as a shopping center in the woodsy contemporary style. The result is a complex and pleasing design, curiously recalling the Monterey Colonial Revival. The school auditorium/theater remains available for theatrical performances and cultural events.

E. Description of particular features subject to preservation in addition to items covered under Section 4.86.120 of the Zoning Ordinance are as follows:

1. Date stamps in concrete sidewalks.
2. All existing picket and ornate wire fences, rock walls and front yard concrete walls shall be repaired and retained.

SECTION III

The intent and purpose of this section is to preserve and protect the Town of Los Gatos' historic heritage, neighborhoods, streetscapes, and districts.

A. Demolitions:

Demolition of any contributing structure is forbidden absent cataclysmic event or upon determination by the deciding body that demolition is necessary for the proper restoration of the structure. In the event of demolition as a result of cataclysmic event, the structure shall be reconstructed to match the structure existing immediately prior to the cataclysmic event or a previous structure on that site.

B. Remodels or Additions:

1. Standards for review as required by Section 29.80.290 of the Town Code as follows:

- a) Architectural Review: Modification of the existing style or overall design of a contributing structure in the district is prohibited. A non-contributing structure may be remodeled into the architectural style and design of a contributing structure in the district (see list of contributors in Section II and Section III, C. herein). New architectural features may be added to the protected exterior facade only upon a demonstration by the applicant proving consistency with the existing architectural style and design as determined by the deciding body. Any proposed new architectural features must be proven to demonstrate architectural excellence, as well as be stylistically accurate and must clearly enhance the existing architectural style and design of the structure. Any uncertainty by the deciding body regarding the consistency, excellence or enhancement of the proposed new features to the existing structure must be resolved by the deciding body against the applicant.
- b) Contributing Structures: The structures identified herein as contributors to the district have been determined to be historically, architecturally or culturally significant. Great care and scrutiny is required to properly remodel or add on to any of the contributing structures so that the structure's historic or architectural integrity is preserved and not destroyed or damaged in the remodeling or addition process (see Section III, A. herein regarding demolitions). The following provisions are guidelines and requirements for the proper historic rehabilitation and alteration of a contributing structure.

- c) Non-Contributing Structures: A non-contributing structure, if not rehabilitated into a contributing style or design as provided herein, should be remodeled or expanded consistent with its existing architectural style and design. Introduction of entirely new architectural styles (i.e. other than Victorian, Craftsman/Bungalow, Mission Revival/Mediterranean) is prohibited.

2. Restoration/Rehabilitation Guidelines

- a) General Guidelines: All protected elements as described in Section III, B.2.(e) herein, of the existing exterior facade must be maintained. Any alteration of or addition to an existing structure shall incorporate and continue the same style patterns and design on the new construction as is on the existing, and also incorporate and continue in a consistent manner the protected exterior elements. Original, existing, protected exterior elements shall be repaired and reused whenever possible. When an addition or remodel requires the use of newly constructed exterior elements, they must be identical in size, dimension, shape and location, and must use the same materials as the existing protected exterior elements (except as provided in Section III, B.2.(e)).
- b) Front yard setbacks: The prevalent front setback for existing houses is 15 feet. Front yard setbacks for new construction may be increased or decreased in accordance with the prevailing setback on the block. (reference Section 29.40.050 and 29.40.055 of the Town Code, note these sections only apply to front yards, not side, rear or side yards abutting streets.)

- c) Heights and proportions: Heights and proportions of additions and alterations shall be consistent with and continue the original architectural style and design. All exterior elements including, but not limited to, rooflines, porches, doorways, windows, trim and siding shall be consistent with and continue the original architectural style and design. New construction should maintain the existing scale and character through compatible design and attention to detail. The height and proportion of an addition or a second story shall not dominate the original structure.
- d) Building Materials: Use of natural/ original construction materials (e.g., real wood siding, rock, brick, shingles, plaster) matching and consistent with existing materials is required. Composite, synthetic, metal, vinyl, plastic or fabricated/ imitation wood products, painted brick or imitation used brick are prohibited. New materials shall identically match original materials in shape, size, dimension, texture and pattern. (metal used as flashing, screening, gutters, and utility services and other traditional elements are acceptable). Upon a demonstration of hardship by the applicant, the decision making body may approve an acceptable alternative to the original building material if use of the original material is unfeasible due to unreasonable cost and commercial availability, or health and safety considerations.
- e) Protected Exterior Elements: The protected exterior elements of a structure include all elements on the building's facades and roof; however, minor structural alterations (e.g., addition of windows, doors, skylights, porches or decks) not visible from the public right-of-way are exempted from the provisions of this ordinance. Except for those minor alternations not visible from

the public right-of-way, the protected exterior elements are defined to include, but are not limited to, doors, windows, glass, porches, posts, railings, stairways, cupolas, gables, bay windows, widows' walks, arbors, siding, chimneys, towers, turrets, trim, mouldings, corbels, plaster features, rock walls, picket fences, shingles, roof lines, eaves and overhangs, colors, gingerbread, shingle siding, tiles, wrought iron and other decorative materials. Other exterior elements of a particular building may be protected as determined by the deciding body. Consistent with these requirements, further specifications regarding particular protected elements is provided as follows:

- (1) Doors: Original doors should be retained and restored. New replacement doors for Victorians should not be flush, but of raised or flat panel design. Front doors generally should be painted not stained (not applicable to Mission Revival/Mediterranean style structures). Screened doors shall be real wood framed of simple design unless patterns can be shown to fit the existing style. Glass or windows in doors shall meet all requirements immediately following.
- (2) Windows and Glass: Original windows, glass and window decorations shall be retained and restored. It is recommended that only the deteriorated portions of the windows shall be replaced rather than the entire window. New or replacement windows shall be wood-sashed and mutined if applicable. Sills, lintels, frames, sashes, mutins, and all decorations shall be identically replaced. All elements of new windows shall be identical in size, shape, proportion, and dimensions as original windows

of the building, or consistent with traditional sizes, proportions and dimensions of buildings of the same architectural style, design and era. Windows must be constructed of real glass and window frames must be constructed of real wood, not vinyl, metal or plastic. All lites (panes of glass) shall be true divided lite, not artificial or snap-in grids. New arched, angled, octagonal and stained glass windows are discouraged. Large expanses of blank exterior walls without windows are discouraged.

- (3) Bay Windows: Size, shape, proportion, dimension, type of foundation, and -roof material and style of bay windows, whether restored or of new construction, must be identical to the original or existing bay windows of the structure. New bay windows may be added to the building in locations where no bay windows previously existed; however, such new bay windows must be identical and replicate the style, design, size, shape and proportion, type of foundation and roof of other bay windows existing on structure; or in the alternative, any said new bay windows must be built in the same size, shape, dimension, proportions, material and type of foundation and roof established by original Victorian structures of the same design and style. New bay windows are permitted only when the applicant proves to the deciding body that said bay window is consistent with existing style, design and character of the contributing structure.
- (4) Chimneys: Wood-framed chimneys are prohibited unless their exteriors are covered with brick or river rock

veneers; stucco Mission, Revival or Mediterranean style houses may have stucco covered chimneys.. Painted metal stove pipe projections of less than four feet are permitted in less visible locations of the structure. The size, shape, dimensions, design and patterns of new and reconstructed chimneys must match those features of existing structure. Chimneys shall not be cantilevered and shall be narrower at the top than at its base.

- (5) Porches: Existing front porches, railings, posts, corbels, roof coverings, ceilings, floors, steps, mouldings, trim; gingerbread, and other decorative features must be retained and restored using original materials, or identical material of same size, shape, proportion, pattern and in same locations. Construction of new porches must consist of materials of same size, shape, dimension and pattern as contributing structures of similar style and design in district and be in appropriate locations on structure. New concrete or masonry porch floors are prohibited on Victorians or Craftsman/Bungalow style houses. Minor alternations of existing porches are permitted only when the applicant proves to the deciding body that said alteration is consistent with the existing style, design and character of the contributing structure.
- (6) Roofs, Gables, Eaves and Overhangs: Roofs shall maintain their original size, shape and pitch. Any changes in roof area, roof line, roof coverings, and eave depth and materials shall be consistent with the existing structure. In general, original gables shall be retained. New gables may be added only where consistent with the

existing style and design and approved by the deciding body. In general, gable ends should be symmetrical. Eaves and fascias are to be constructed of wood. Roof coverings of fireproof composition materials and dark colors in a heavy profile are acceptable where they are made to resemble wood, if they are compatible with the architectural style of the building. Mission Revival or Mediterranean style structures shall have tile roofs of a color, texture, thickness and shape to look like the original clay roof tile. Plastic and modern style tiles are prohibited.

(7) Siding: Siding materials and placement on structure shall be appropriate to the existing style and design. All existing siding is to be restored and retained wherever possible.

a. Wood siding, (Victorian/Craftsman): Siding must be real wood and not a composite, synthetic or fabricated wood product. Metal and vinyl siding products are prohibited. New siding must identically match existing in size, depth, width, pattern, and must match the existing cut or bevel in siding in angle, slope, type width and depth of cut, if any. Old deteriorated shingles may be replaced, however, new shingles must match existing shingles in size, shape, dimension and pattern. Siding material must run from the foundation to the roof, unless existing pattern of house varies, in which case it must match pattern.

- b. Stucco Siding, (Mission Revival/Mediterranean/Craftsman): Stucco and stucco pattern must be retained and duplicated to identically match existing. The stucco should be sand textured, finished and colored to match existing, or to match other contributing structures of the same style in the District.
- (8) Fences/Walls: All existing picket and ornate wire fences, rock walls and front yard concrete walls shall be repaired and retained. Replacement or newly constructed fences or walls shall match those existing on the property, or shall match those of other contributing properties on that block. Introduction of new rock wall patterns, or new types of rocks or veneers in walls, not already existing in the district, is prohibited. Mortar should also match existing in color, texture, joint width and profile. New fencing shall be of open design, shall be constructed of wood, ornate wire (does not include chain link) or wrought iron and shall be consistent with those existing in the district. Covered gateways are permitted. Side and rear yard fencing shall be of traditional construction and materials and shall be consistent with prevalent fencing in the district.
- (9) Decorative Trim/Mouldings/Gingerbread: All existing to be repaired and retained. Replacement must match existing in materials, size, shape; dimension, location and pattern. Addition of new trim, moulding, gingerbread, etc., on new construction must be located and continued in the existing pattern around the exterior of the structure so

as to maintain consistency with the original style and design. Excessive or inappropriate use of gingerbread or other decorative materials is prohibited. Addition of new trim, moulding, gingerbread, etc. on areas where not previously existing is discouraged.

- (10) Colors: For Victorians, traditional 3 or 4 color paintings patterns are encouraged. For Craftsman, traditional colors are encouraged. For Mission Revival/Mediterranean, the traditional use of earth tones and red-hued roofing materials is required.
- (11) Garages: Style, roof pitch, proportions, and overall design of the garage (or carriage house, etc.), as well as building materials and architectural details shall be consistent with those of the era of the house. Exterior features of garages which are more modern or contemporary than the style of the house for which the garage is being built are discouraged. This includes features such as aluminum or roll up doors, aluminum frame windows, etc. This restriction applies only to features visible from a public right-of-way. Garages should be detached (may be attached by a breezeway) and set back behind the front facade of the house.

1

- f) Interior Features: Only in cases where the owner desires to take advantage of the 1976 Tax Reform Act, the owner must retain original material, architectural features, hardware, original paint colors, plaster, wallpaper, etc., wherever possible. Repair and restore original materials wherever possible or replace with identical, replicated materials. Further information regarding consistency with interior remodels is available upon request.

C. Construction of New Structure or Redesign or Remodel of Non-Contributing Structure into a Contributing Style:

1. Entire New Structure: Construction of a new structure must be built in the style and design of contributing structures in the district. Exact duplication is neither required or encouraged. Strict adherence to achieving consistency with a traditional, recognized architectural style and design of a contributing structure in the district is required. New Victorian and Craftsman style structures must accurately replicate the traditional style, design and integrity of those contributing structures in the district. All doubts or insufficiencies regarding an applicant's proposal regarding the consistency of a proposed new structure, style and design with that of a contributing structure in the district are to be resolved against the application by the deciding body'
2. Remodel Non-contributor into Contributing Style and Design: An owner who wishes to remodel a non-contributing structure into the style and design of a contributing structure in the district may do so. However, the same requirement of Section III, C.I. herein, must be adhered to by the applicant.
3. Standards for Review:
 - a) Intent and Purpose:

The intent and purpose of this section is to protect Los Gatos' historic heritage, neighborhoods, streetscapes, and districts. Great care and scrutiny is required to properly build or remodel a structure so that it becomes an asset to a historic district. Approvals for applications under this section shall be granted only where these guidelines have been met.
 - b) Acceptable Architectural Styles and Designs: In general, Victorian, Craftsman/Bungalow, and Mission Revival/Mediterranean styles are the contributors to Los Gatos'

historic districts. An applicant must produce photographs, counts, and documentation of the location of existing structures of that style in the district or reference materials indicating consistency with contributing styles in the district. All exterior elements subject to review shall be consistent with the proposed style.

4. New Construction/Remodeling into Contributing Style and Design - Construction Guidelines:

- a) Front yard setbacks: The prevalent front setback for existing houses is 15 feet. Front yard setbacks for new construction may be increased or decreased in accordance with the prevailing setback on the block. (reference Section 29.40.050 and 29.40.055 of the Town Code these sections only apply to front yards, not side, rear or side yards abutting streets). The front facade shall be parallel to the street.
- b) Heights and proportions: Heights and proportions of altered or new structures shall be consistent with those of contributing structures of the same style in the district. They should not be significantly taller, more massive, or in greatly different proportions from other contributing structures of the same style in the district.
- c) Required Building Materials: Use of natural construction materials (e.g. real wood siding, stucco, rock, brick, wood shingles, plaster) is required. Composite, synthetic, metal, vinyl, plastic or fabricated/ imitation wood products, painted brick. or imitation used brick are prohibited. Materials used shall be the same as those used in existing contributing buildings of the same style in the District (except that masonry or stone veneers on chimneys are acceptable).

Upon a demonstration of hardship by the applicant, the decision making body may approve an acceptable alternative to the original building material if use of the original material is unfeasible due to unreasonable cost and commercial availability, or health and safety considerations.

- d) **Exterior Elements Subject to Review:** To be reviewed are: all elements on the building's facades and roof, including but not limited to, doors, windows, glass, porches, posts, railings, stairways, cupolas, gables, bay windows, widows' walks, arbors,' siding, chimneys, towers, turrets, trim, mouldings, corbels, plaster features, rock walls, picket fences, shingles, roof lines, eaves and overhangs, colors, gingerbread, shingle siding, tiles wrought iron and other decorative materials. Other exterior elements of a particular building may be protected as determined by the deciding body. Consistent with these requirements, further specifications regarding particular protected elements is provided as follows:

- (1) **Doors:** Doors should not be flush but of raised or flat panel design and painted, rather than stained, on. Victorian and Craftsman-Bungalow style structures. Screened doors shall be real wood framed of simple design unless patterns can be shown to fit the existing style. Glass or windows in doors shall meet, all requirements immediately following.
- (2) **Windows/Glass:** New or replacement windows shall be wood sashed and, if mutins are appropriate, wood mutined. All elements of new or replacement windows shall be consistent with the traditional' sizes and proportions of those in buildings of the same architectural style in the District (e.g. the long, narrow windows of Victorian Architecture).

Victorian style structures shall have windows constructed in the proportion and dimensions matching original Victorians. Vinyl, aluminum or other types of window frames are prohibited. All lites (panes of glass) shall be individual lites, not artificial or snap-in grids. Arched windows are discouraged in Victorian styles. Octagonal windows are discouraged in Victorian, Craftsman/Bungalow, and Mediterranean/Mission Revival styles.

- (3) Bay Windows: Size, shape, proportion, scale, materials, type of foundation or support, type of decorative elements, and style of new bay windows must replicate those in existing contributing structures of the same architectural style in the District. In general, bay windows are only appropriate to Victorian styles. Victorian style structures shall have windows constructed in the proportion and dimensions matching original Victorians.
- (4) Chimneys: Chimneys of Victorian or Craftsman/Bungalow styles shall be of reinforced masonry or stone, or wood frame with brick or stone/rock veneer and be smaller at the top than at the bottom. Chimneys on Mission Revival/Mediterranean buildings may also be of a stucco to match the exterior of the building.
- (5) Porches: New porches must be of the same materials, relative size, shape, dimension, and having the same type of decorative elements as those of contributing structures of the same style in the district. New concrete or masonry porch floors and steps are prohibited on Victorian or Craftsman/Bungalow style houses.

- (6) Roof Lines. Gables, Eaves and Overhang: For Victorian and Craftsman/Bungalow style structures, fire retardant wood shingles are the preferred material; fireproof composition materials are acceptable in dark colors and with a heavy profile, especially those which resemble wood. Mission Revival/Mediterranean style structures shall have tile roofs of a color, texture, shape, and thickness to look like traditional tiles. Plastic and modern style tiles are prohibited.
- (7) Siding: Siding on Victorian or Craftsman/Bungalow style structures must match those of a contributing structure of the same style in the District in size, depth, width, material, pattern, cut or .bevel, angle; slope, type; and width or depth of cut, if any.
- (a) Wood siding (Victorian/Craftsman): All wood siding material shall be real wood and not .a composite or fabricated wood product. Shingles must also be of a size, shape, dimension, and pattern to be consistent with singles of one or more contributing building of the same style in the District. Siding materials must run from the foundation to the roof unless the applicant can cite other contributing houses of the same style in the District on which the siding pattern varies in the manner proposed.
- (b) Stucco Siding (Mission Revival/Mediterranean/Craftsman): Stucco pattern, color, finish, and texture should closely resemble that on other houses of the same style in the district.

- (8) Picket Fences/Rock Walls/Arbors: Picket fences/rock walls/arbors shall match or be very similar to those on a contributing building of the same style in the District. Excessive or inappropriate use of "gingerbread" or other decorative elements is prohibited. New fencing shall be of open design, shall be constructed of wood, ornate wire (does not include chain link) or wrought iron and shall be consistent with those existing in the district. Covered gateways are permitted. Side and rear yard fencing shall be traditional construction and materials and shall be consistent with prevalent fencing in the district.
- (9) Decorative Trim/Mouldings/Gingerbreads: Excessive or inappropriate use of gingerbread or other decorated elements is prohibited. Size, shape, dimension and location of these decorative materials shall be consistent with that on other contributing structures of same style and design in the district.
- (10) Colors: For Victorians, traditional 3 or 4 color paintings patterns are encouraged. For Craftsman, traditional colors are encouraged. For Mission Revival/Mediterranean, the traditional use of earthtones and red-hued roofing materials is required.
- (11) Garages: Style, roof pitch, proportions, and overall design of the garage (or carriage house, etc.), as well as building materials and architectural details shall be consistent with those of the era of the house. Exterior features of garages which are more modern or

contemporary than the style of the house for which the garage is being built are discouraged. This includes features such as aluminum or roll up doors, aluminum frame windows, etc. This restriction applies only to features visible from a public right-of-way. Garages should be detached (may be attached by a breezeway) and set back behind the front facade of the house.

- R All structures (including accessory buildings) included in the district are regulated by this ordinance and subject to all of the provisions of Article VIII, Division 3 of the Town Code. However, the permit requirements of Section 29.80.260 of the Town Code only apply to work which is considered a material change. A material change is any exterior alteration for which a building permit is required or which will affect the protected exterior elements as defined in Section II, B.2.(e) herein. This does not include painting and ordinary maintenance which do not require a permit.

SECTION IV

This Ordinance takes effect 30 days after the date it is adopted. Within 15 days after this Ordinance is adopted, the Town Clerk shall cause it to be published once in a newspaper of general circulation published and circulated in the Town.

This Ordinance was introduced at a regular meeting of the Town Council of the Town of Los Gatos on October 5, 1992, and adopted by the following vote as an ordinance of the Town of Los Gatos at a meeting of the Town Council of the Town of Los Gatos on October 19, 1992.

COUNCIL MEMBERS:

AYES: Randy Attaway, Joanne Benjamin, Steven Blanton, Brent N. Ventura
Mayor Eric D. Carlson

NAYS: None

ABSENT: None

ABSTAIN: None

SIGNED: /s/ Eric D. Carlson
MAYOR OF THE TOWN OF LOS GATOS
LOS GATOS, CALIFORNIA .

ATTEST:

/s/ Marian V. Cosgrove
CLERK OF THE TOWN OF LOS GATOS
LOS GATOS, CALIFORNIA

BIBLIOGRAPHY

Bloomfield, Anne. Los Gatos Historic Resources Inventory, 1991.

Rifkind, Carole. A Field Guide to American Architecture. New York, Bonanza Books, 1980, 1986.

HELPFUL REFERENCES

American Life Foundation. "Gordon-Van Tine Co. Architectural Details 1915", Catalogue, New York, American Life Foundation. 1985.

Amrhein, James E., S.E. Residential Masonry Fireplace and Chimney Handbook. Los Angeles, Masonry Institute of America. 1989.

Blumenson, John J.G. Identifying American Architecture. Nashville, American Association for State and Local History, 1977, 1981.

Bruntz, George G. History of Los Gatos. Santa Cruz, Western Tanager Press (Valley Publishers). 1983.

Howard, Hugh. How Old is this House? A Skeleton Key to Dating and Identifying Three Centuries of American Houses. New York; Farrar, Straus and Giroux for Home Renovation Associates. 1989.

Kariotis, John, Roselund, Wells and Krakower, Mike. The Engineer's View. Loma Prieta: Historic Buildings. Earthquake Damage and Seismic Strengthening. California, California Preservation Foundation. 1991.

Klein, Marilyn W. Clues to North American Architecture. Markham, Ontario; Fitzhenry & Whiteside Limited. 1985.

McAlester, Virginia & Lee. A Field Guide to American Houses. New York, Alfred A. Knop. 1984, fourth printing 1986.

Merritt, John. Loma Prieta: Seismic Safety and Historic Building. California, California Preservation Foundation. 1990.

Moss, Roger. Century of Color. Watkins Glen, New York; American Life Foundation 1981.

Myers, John H., revised by Hume. Gary L. "Aluminum and Vinyl Siding on Historic Buildings". Volume 8, Preservation Briefs. Washington, D.C.; U.S. Government Printing Office.

Myers, John H. "The Repair of Historic Wooden Windows". Volume 9, Preservation Briefs. Washington, D.C.; U.S. Government Printing Office.

Nelson, Lee H., FAIA. "Architectural Character: Identifying the Visual Aspects of Historic Buildings, as an Aid to Preserving Their Character". Volume 17, Preservation Briefs. Washington, D.C.; U.S. Government Printing Office.

Park, Sharon C., AIA. "The Use of Substitute Materials on Historic Buildings Exteriors". Volume 16, Preservation Briefs. Washington, D.C.; U.S. Government Printing Office.

Prentice, Helaine Kaplan and Prentice, Blair. Rehab Right. How to Realize the Full Value of your Old House. City of Oakland Planning Department. Berkeley, Ten Speed Press, 1978, 1986.

Stahl, Frederick A. A Guide to the Maintenance, Repair, and Alteration of Historic Buildings. New York, Van Nostrand Reinhold Company. 1984.

Sweetser, Sarah M. "Roofing for Historic Buildings" Volume 4, Preservation Briefs. Washington, D.C.; U.S. Government Printing Office.

U.S. Department of the Interior National Park Service The Secretary of the Interior's Standards for Rehabilitation and Guidelines for Rehabilitating Historic Buildings (Revised 1989). Washington, D.C.; U.S. Department of the Interior National Park Service Preservation Assistance Division.

Weeks, Kay D. "New Exterior Additions to Historic Buildings: Preservation Concerns". Volume 14, Preservation Briefs. Washington, D.C.; U.S. Government Printing Office.




Exhibit A

TOWN OF LOS GATOS

University-Edelen Historic District Boundaries

As Established by Ordinance 1844 On April 15, 1991